EU type certificate

CERTIFICATE No. 24/07654/00/0161

PPE TYPE MASK COVERS
REF: FRS2400.UE-GSV RESPIRATOR FLAME RESISTANT FR-SHIELD ONE-SIZE (EU) FOR ELIPSE HALF MASK RESPIRATOR





AITEX, Notified Body No. 0161 for the application of Regulation (EU) 2016/425 of the European Parliament and of the Council of 9th March 2016, in which the essential health and safety requirements that Personal Protective Equipment (PPE) must comply with.

CERTIFIES The Company:

ORIGINAL BUFF,S.A
França 16 (Pol.Ind)
ES-08700 IGUALADA
BARCELONA
Spain

As a manufacturer

ENAC
CERTIFICACIÓN
ISO 17065
Nº155 / C-PR364

Rev. 2
This revision cancels and replaces the previous

ASOCIACIÓN DE INVESTIGACIÓN DE LA INDUSTRIA TEXTIL Y COSMÉTICA (AITEX)Carretera de Banyeres, 10 · Alcoy (Alicante) 965542200 · info@aitex.es
www.aitex.es

CERTIFICATE No. 24/07654/00/0161

Has obtained EU TYPE EXAMINATION in compliance with what is set out in Annex V (module B) in Regulation (EU) 2016/425 and in agreement with the applicable test procedures and technical specifications

Designed for the protection of the neck, according to the following standard/s:

- EN ISO 13688:2013+EN ISO 13688:2013/A1:2021 Protective clothing - General Requirements
- EN ISO 11612:2015 against thermal risks of limited flame spread (A1+A2), convective heat (B2), radiant heat (C1) and contact heat (F1)
- EN 1149-5:2018 against the risk of accumulation of electrostatic loads
- Risk against heat or fire, wildland firefighting protection assessed by sizing in point 4. 4 of EN ISO 16073-9:2020 (Length 32,0 cm), limited flame spread in EN ISO 15025:2016 procedure A (Woven fabric 0s ignition and incandescence, no perforation and no residues; assembly 0s ignition and incandescence, no perforation and no residues), heat resistance of yarn in EN ISO 3146: 2000 (no melting), fabric/assembly lining heat resistance to ISO 17493:2016 (Woven fabric ±1% ; Assembly ±3%), convective heat to EN ISO 9151: 2016 (HTI^a 24 = 11.8), radiant heat in EN ISO 6942:2022 ($RHTI^a$ 24 = 14.2 ; $RHTI^a$ 24-12 = 6.5), burst strength after exposure to radiant heat of fabric in EN ISO 13938-1:2019 (2388kPa), burst strength at seams in EN ISO 13938-1: 2019 (Woven and knitted fabric 2994 kPa; Woven fabric 2575 kPa), dimensional stability in EN ISO 5077:2008 (Width -1%; Length -2%), water vapour resistance in EN ISO 11092:2014 (4.31 m^2Pa/W) for compliance with point 3. 6 of EU Regulation 2016/425.

Tests carried out after 5 washing cycles 40ºC.
Having achieved the performance requirements specified in conformity assessment report No. **2024EP4078UE** and the PPE's Technical Documentation.

Description of the PPE:

Mask cover made of black woven fabric / black knitted fabric. The PPE is available in one size.

The materials that form the PPE, are described in the conformity assessment report nº **2024EP4078UE**.

The PPE is available with the following variants:

- PPE can be presente with two versions, "FRS2400.EU - GVS RESPIRATOR FLAME RESISTANT FR-SHIELD ONE-SIZE (EU) FOR ELIPSE HALF MASK RESPIRATOR" for European Union and "FRS1400.US - GVS RESPIRATOR FLAME RESISTANT FR-SHIELD ONE-SIZE (US) FOR ELIPSE HALF MASK RESPIRATOR" for United States.

It shall be the manufacturer's responsibility to provide specific information of this certificate and the tested levels of protection.

The CAT. III PPE shall only be used in conjunction with one of the conformity assessment procedures according to module C2 or module D described in article 19 letter c) of the Regulation (EU) 2016/425.

Date: 14/11/2024 17:09:47
Digitally Signed by:SILVIA DEVESA VALENCIA - NIF:21657673E

Date of expiry
24/10/2029
* Date (dd/mm/yyyy)

Silvia Devesa Valencia
Laboratory Subdirector and Innovation