STAHLWILLE®



Duo work spotlight

13139 DL

Product no.	**77490020**
GTIN	**4018754360642**
Model	**13139 DL 11500**

Label.

Duo work spotlight 11.500/ 5.750/ 2.000 lm

Properties.

- 2 fold-out 36 W SMD LED modules (can be swivelled and rotated 180°)
- adjustable brightness with 3 brightness levels: 100% (11,500 lm) / 50% (5,750 lm) / 20% (2,000 lm)
- lighting duration/brightness: 1.5 h (11,500 lm) / 3 h (5,750 lm) / 6 h (2,000 lm)
- lighting range: max. 21 m
- switch for changing light colours: 4,000K (3,500 lm in mains operation), 6,500K (3,700 lm in mains operation)
- lighting duration: up to 6 h
- dual power supply with mains and battery operation
- rechargeable via USB-A connection
- charging time: approx. 3 h
- integrated Li-ion battery pack 14.8 V/4,000 mAh/29.6 Wh with safety electronics
- with power bank function
- charging control, warning and remaining capacity display
- height-adjustable tripod: 1,171–1,980 mm, with handle, cable reel and ground spikes
- removable light head with 2 rotating hooks and 4 holding magnets
- protection class: IK07/IPX4
- accessory: power supply unit with 5 m cable

Benefits.

2 rotatable and swivelling LED spotlights enable even and precise light alignment at any angle.

Intense luminosity up to 11,500 lumens with 3 brightness levels and 2 colour temperatures (4,000K & 6,500K).

Up to 6 hours of light output (depending on the operating mode) thanks to the permanently installed Li-ion battery with safety electronics (14.8 V/4,000 mAh/29.6 Wh).

Practical power bank function via USB port.

Robust telescopic stand with integrated cable reel prevents tripping hazards and keeps things tidy.






Product highlights.



Bright performance.
The two powerful LED elements achieve a luminosity of up to 11,500 lumens. In addition, the colour temperature can be flexibly adjusted to different working conditions: 4,000K (warm white) for pleasant, glare-free lighting, or 6,500K (cool white) for high-contrast, daylight-like light.



For indoor and outdoor use.
Our work spotlight is suitable for both indoor and outdoor use. High-quality materials and IPX4 protect it from impacts, scratches and splash water in harsh workshop environments.



Versatile mounting options.
Thanks to the practical magnetic holder, the removable light can be securely attached to metal surfaces. It can also be hung up using two fold-out, rotatable hooks.



Flexible and safe.
The robust telescopic stand can be extended to a height of almost 2 m and, thanks to fold-out feet and integrated ground spikes, offers a stable footing and optimal lighting in any work situation. The Duo spotlight can be folded up conveniently and compactly for transport. The integrated cable reel ensures tidy storage of the cable, prevents tripping hazards and increases work safety.



Power bank function via USB port.
The construction spotlight can be used as a power bank via a USB connection to charge mobile phones or other devices, for example. The battery is charged via a type A connection.

Technical attributes.

variable height	max. 1980 mm
Battery type	Li-ion 14.8 V / 4,000 mAh
Brightness	11.500/ 5.750/ 2.000 lm
Protection class	IK07/ IPX4

Logistics data.

Product no.	77490020
GTIN	4018754360642
Weight (g)	5960 g
Volume (packaged, dm3)	28.576 dm3
Packing standard	1
WEEE/ElektroG	Kleingeräte B2C
Customs tariff no.	85131000
Country of origin AWR	CHINA
Region of origin	Ausländischer Ursprung
Depth mm (IFS)	940
Width mm (IFS)	190
Height mm (IFS)	160
Weight (gross, kg)	7,450
Weight PAP (kg)	0,650
Weight PVC (kg)	0,000
Length (packaged, mm)	940
Width (packaged, mm)	190
Height (packaging, mm)	160

GTIN.



Images.











STAHLWILLE Eduard Wille GmbH
Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0
info@stahlwille.de · www.stahlwille.com
© STAHLWILLE Eduard Wille GmbH, Wuppertal